



EAX 2512

Sat IF branch (dual)

Order no.: 20510035



Sat IF splitter - 5-862 u. 4 x 950-2150 MHz - 5 x 2-way splitter 12 dB in one go. - F-connectors - cascadable with EXR 5-series multi-switch system

- Two-way tap and two-way distributor for the Sat IF distribution system (4 x Sat IF)
- For signal distribution in very large satellite IF systems with cascades of 5 multi-switches
- Remote feed capable via input ↔ trunk output (4 x Sat IF); isolating capacitors at the branch outputs)
- For indoor installation
- Two-way tap for connecting e.g. two 5-way multi-switch cascades to one trunk line
- Five dual feeders (4 x Sat IF and 1 x terr. range) in one housing
- Cascadable with additional EAX 2512 or EBX 2520

Status 08/2023

Technische Daten / Technical Data:

Type:	EAX 2512
Order no:	20510035
Inputs:	1 x terrestrial / 4 x Sat IF
Throughput attenuation (input -> trunk-output):	1.5 → 2 ¹⁾ / 0.8 → 1.5 ¹⁾ dB
Connection attenuation (input -> branch/distribution output):	12 / 13 -> 11 ¹⁾ dB
Decoupling strain:	50 dB
Max. Remote power supply current per sat level:	1000 mA
Frequency range:	5 – 862 MHz 950 – 2150 MHz
Decoupling of branch/distribution outputs:	30 / 30 dB
Connections:	F-Connectors
Dimensions (W x H x D):	112 x 148 x 54.5 mm
Packaging unit/weight:	1 (10)/0.39 pcs./kg

¹⁾ Frequency-dependent attenuation

Downloads

- [EAX 2512 - Technische Daten / Technical Data \(Version: 08/2023 - Größe: 1.70 MB\)](#)
- [EAX 2512 - Produktdatenblatt \(Version: 07/2023 - Größe: 804.93 KB\)](#)
- [EAX 2512/EBX 2520 - Bedienungsanleitung | User Manual \(Version: gb - Größe: 729.48 KB\)](#)



Produkt Galerie:

