



EBX 2920

Sat IF distributor (double)

Order no.: 20510022



- Two-way tap and two-way distributor for the Sat IF distribution system (8 x Sat IF)
- For signal distribution in very large satellite IF systems with cascades of 9 multi-switches
- For indoor installation
- Two-way distributor for distributing the trunk lines to two 9-way multi-switch cascades
- Nine dual distributors (8 x Sat IF and 1 x terr. range) in one housing
- Suitable for remote feed via input <-> Trunk output (8 x Sat IF) and via distribution output horiz. low (diode decoupling to the trunk output); isolating capacitors at the other distribution outputs.
- Cascadable with additional EBX 2920 or EAX 2912

Technische Daten / Technical Data:

Type:	EBX 2920
Order no:	20510022
Inputs:	1 x terrestrial / 8 x Sat IF
Throughput attenuation (input -> trunk-output):	4.0 / 4.0 dB
Connection attenuation (input -> branch/distribution output):	4.0 / 4.0 dB
Decoupling strain:	40 dB
Max. Remote power supply current per sat level:	1000 mA
Frequency range:	5 – 862 MHz 950 – 2150 MHz
Decoupling of branch/distribution outputs:	25 / 30 dB
Connections:	F-Connectors
Dimensions (W x H x D):	112 x 228 x 54.5 mm
Packaging unit/weight:	1 (10)/0.6 pcs./kg

Downloads

- [EBX 2920 - Produktdatenblatt \(Version: 08/2023 - Größe: 179.22 KB\)](#)
- [EAX 2912/EBX 2920 - Bedienungsanleitung | User Manual \(Version: 07/2022 - Größe: 565.08 KB\)](#)



Produkt Galerie:

