



KEL 300/W

Wideband feed system

Order no:201500004



- Compatible with the OSW 1310/6 and OSW 1550/6 optical transmitters
- Mandatory if terrestrial signals are also to be fed in
- Suitable for satellite antennas with a 40 mm LNB mount (KEA 650/750/850/1000)
- Integrated 2.4 GHz low-pass filter

Status 10/2024

Technical data:

Type:	KEL 300/W
Bestell-Nr.:	201500004
Input frequency:	10.70 – 12.75 GHz
Gain:	typ 55 dB
Output frequency:	300 – 2350 MHz
Oscillator frequency (L.O.):	10.4 GHz
Supply voltage:	10 – 20 V
Power consumption:	max.2 W
Output:	2 x F socket
LNB mount dimensions:	Ø 40 mm
Zul. Ambient temperature:	-30 to +60 °C
Dimensions (W x H x D):	141 x 89 x 63 mm
Packaging unit/weight:	1/0.35 pc/kg

Downloads

- [KEL 300/W - Produktdatenblatt \(Version: 02/2024 - Größe: 130.90 KB\)](#)
- [KEL 300/W - Bedienungsanleitung \(Version: 10/2023 - Größe: 642.15 KB\)](#)



Produkt Galerie / Product Gallery:

