


Order number: 274209

Open text field 1:

- Compliant with: EN 60728-11 and EN 50083-2
- Stable die-cast housing
- With screw and claw fastening, suitable for flush mounted boxes with diameter 55-65 mm
- Can be combined with almost all installation programs
- Satellite single connection box, 3-way, for stub and star distribution systems in communal and satellite house distribution systems
- With DC voltage passage via satellite connection (max. 24 V/320 mA, 22 kHz- and DiSEqC™ signal)



ESD 30

Product information "ESD 30"

Single outlet, 3-way- 2 x 5-862 and 950-2400 MHz - DC voltage passage via satellite connection - Connection loss: VHF 3.5 dB, UHF 4 dB, sat 1 dB

Type:	ESD 30
Order no.:	274209
Connection loss - Radio 5-47 MHz (Return path):	5,0 dB
Connection loss - Radio 47-68 MHz (Band I):	3,5 dB
Connection loss - Radio 87.5-108 MHz (FM):	3,5 dB
Connection loss - Radio 118-470 MHz (VHF):	3,5 dB
Connection loss - Radio 470-1006 MHz (UHF):	4,0 dB
Connection loss - TV 5-47 MHz (Return path):	5,0 dB
Connection loss - TV 47-68 MHz (Band I):	3,5 dB
Connection loss - TV 87.5-108 MHz (FM):	3,5 dB
Connection loss - TV 118-470 MHz (VHF):	3,5 dB
Connection loss - TV 470-1006 MHz (UHF):	4,0 dB
Connection loss - Sat 950-2150 MHz (Sat IF):	1,0 dB
Connection loss - Sat 2150-2400 MHz (Sat IF):	2,0 dB
Packaging unit/weight:	10 (50)/0.85-1.1 pc/kg

¹⁾ Between two subscribers



Hersteller: Kathrein