

Order number: 21110022

Open text field 1:



- Compliant with: EN 60728-11 and EN 50083-2
- Switches off the connected receiver if it is not using the unicable DiSEqC™ command set in accordance with EN 50494 or EN 50607 (switches off voltage from satellite connection to input at +18 V after approx. 400 ms)
- Overload protection with electronic fuse and decoupling diodes
- ERA 14 to be used as the terminating resistor
- Stable die-cast housing
- With screw and claw fastening, suitable for flush mounted boxes with Ø 55-65 mm
- Can be combined with almost all installation programs
- Connections: TV - IEC connector | Radio - IEC socket | Sat IF - F socket
- Directional coupler outlet, 3-way, for loop-through systems in unicable systems complying with EN 50494 or EN 50607.
- With DC voltage passage to trunk line via satellite connection (max. 24 V/400 mA, 22 kHz and DiSEqC™-Signal)



Hersteller: Kathrein

ESU 36

Product information "ESU 36"

Loop-through box for unicable system - 3-way - 87-108 and 47-68/118-862 and 950-2150 MHz - DC voltage passage via satellite
 - Connection loss: FM 11 dB, VHF/UHF/sat 10 dB

Type:	ESU 36
Order no.:	21110022
Connection loss - Radio 47-68 MHz (Band I):	- dB
Connection loss - Radio 87.5-108 MHz (FM):	15 dB
Connection loss - Radio 118-470 MHz (VHF):	- dB
Connection loss - Radio 470-862 MHz (UHF):	- dB
Connection loss - Radio 950-2150 MHz (Sat IF):	- dB
Connection loss - TV 47-68 MHz (Band I):	14 dB
Connection loss - TV 87.5-108 MHz (FM):	- dB
Connection loss - TV 118-470 MHz (VHF):	14 dB
Connection loss - TV 470-862 MHz (UHF):	14 dB
Connection loss - TV 950-2150 MHz (Sat IF):	- dB
Connection loss - Sat IF 47-68 MHz (Band I):	- dB
Connection loss - Sat IF 87.5-108 MHz (FM):	- dB
Connection loss - Sat IF 118-470 MHz (VHF):	- dB
Connection loss - Sat IF 470-862 MHz (UHF):	- dB
Connection loss - Sat IF 950-2150 MHz (Sat IF):	14 dB
Through loss VHF:	0,7 dB
Through loss UHF:	0,8 dB
Through loss Sat-IF:	1,5 dB
Internal decoupling ¹⁾ Sat IF:	> 32 dB
Internal decoupling ¹⁾ VHF/UHF:	> 42 dB
Packaging unit/weight:	10 (50)/1.0 pc/kg

¹⁾ Between two subscribers