

**Order number:** 20510072**Open text field 1:**

Wavelengths: 1310 and 1550 nm  
Bandwidth: +/- 40 nm  
Compact dimensions due to mini coupler  
Low polarisation sensitivity  
High stability and reliability  
Outstanding mechanical and environmental properties  
Single mode  
For indoor installation  
Outstanding CLIK! plug connections

**Hersteller:** Kathrein

## OVC 425

### Product information "OVC 425"

Optical 4-way distributor 7.7 dB (25/25/25/25%) - CLIK! connections - Wavelength 1310 and 1550 nm - Bandwidth +/- 40 nm;

<b>Type:</b>	OVC 425
<b>Order no.:</b>	20510072
<b>Return loss:</b>	Min. 50 dB
<b>Directivity:</b>	Min. 55 dB
<b>Operating bandwidth:</b>	+/- 40 nm
<b>Splitting ratio:</b>	25
<b>Insertion loss:</b>	Typ. 6,8 dB
<b>Operational wave lengths:</b>	1310 und 1550 nm
<b>Operating temperature:</b>	-40 to +85 °C
<b>Dimensions:</b>	93 x 42,5 x 15 mm
<b>Packaging unit/weight:</b>	1 (40)/0.035 pc/kg

### Mehr Bilder zu "OVC 425"

