

Order number: 26210086**Open text field 1:**

Monitoring transponder for compact and house connection amplifiers, and optical compact receivers (see table)
Monitoring of various parameters, e.g. voltage, current drain, internal temperature etc.
Operation of ingress control switch on units with appropriate equipment
Transmission using DOCSIS or EURODOCSIS protocol
Frequency-agile in the range 5-65 and 90-862 MHz
10/100 BaseT-RJ 45 interface to headend for servicing

Hersteller: Kathrein

TVM 1000

Product information "TVM 1000"

DOCSIS/ EuroDOCSIS 2.0 monitoring transponder, frequency-agile

Type: TVM 1000**Order no.:** 26210086**Max. output level:** 113-118 dB μ V**Output frequency range:** 5-65 MHz**Suitable for device type:** VGO 939-1G, VGF 939-1G, VOS 952-1G, VOS 953-1G, ORA 9222-1G, ORA 9022-1G, ORA 920/921, VGP 9033-1G, VGP 9041 ab Stand A02 (Nov. 2008), VGF 9030/9040, VGP 9236-1G, VGP 9240**Input frequency range:** 90 – 862 MHz**Input level range:** 48-78 dB μ V**Transmission protocol:** DOCSIS/EuroDOCSIS 2.0**Power consumption:** 3,5 W