


Order number: 272327

Open text field 1:

- Impedance: 75  $\Omega$
- Compliant with: EN 60728-11 and EN 50083-2
- Thanks to wide frequency range of 0.15-2150 MHz suitable for universal use for individual and communal units, CATV house distribution systems and satellite reception systems
- For indoor installation



Hersteller: Kathrein

**EAC 12****Product information "EAC 12"**

1-way tap 11 dB, 0.15-2150 MHz, clamp connection, screening class A in accordance with CENELEC EN 50083-2

Type:	EAC 12
Order no.:	272327
Frequency range:	0,15-2150 <sup>1)</sup> MHz
Tap attenuation:	10.5 dB
Through loss 0.15-47 MHz/47-862 MHz/862-2150 MHz:	1,5/1,1/1,8 dB
Directional attenuation (output -> tap) 47-2150 MHz/minimum value:	$\geq 28,5$ <sup>2)</sup> /20,5 dB
Clamp-connection $\varnothing$ :	Centre conductor
Dimensions:	88,5 x 30 x 75 mm
Packaging unit/weight:	1 (100)/0.20 pc/kg

<sup>1)</sup> EAC 12/EAC 16: Data variation in LMK range

<sup>2)</sup> Relative to 40 MHz, -1.5 dB/Octave

Mehr Bilder zu "EAC 12"

