


Order number: 205500003

Open text field 1:

- High-quality optical CLIK! connection
- Easy installation planning with the "CLIKulator" program. Address: <http://clikulator.com/kathrein>
- Transmission of the entire digital terrestrial frequency range incl. VHF
- For indoor installation
- Optical quad receiver (switchable outputs)



Hersteller: Kathrein

OEC 44 micro

Product information "OEC 44 micro"

Optical receiver with switchable outputs, optical input CLIK! connection, output F connectors, optical performance (min-max) -8 to -14 dBm

Type:	OEC 44 micro
Order no.:	205500003
Return loss (RF outputs):	Typ. 10 dB
Return loss (optical input):	Min. 45 dB
Wavelength (optical input):	1310 nm
Input power (min-max) (optical input):	-14 to -8 dBm
RF total output level @ optical -21 dB (RF outputs):	Typ. 77 (Digital-TV); typ. 80 (Sat) dBμV
Bandwidth (RF outputs):	87,5-862/950-2150 MHz
Satellite control output (RF outputs):	14/18 V; 0/22 kHz
Operational voltage:	- V (DC) /mA
LED information:	Mode indicator
Connection type (RF outputs):	F socket
Power consumption:	5 W
Power supply voltage:	220-240/50-60 V~/Hz
Connection type (optical input):	CLIK!
RF outputs:	4 x Sat and 1 x digital terrestrial
Operating temperature:	+5 to +45 °C
Dimensions (W x H x D):	99 (ohne Buchsen) x 138 x 50 mm
Packaging unit/weight:	1/0,302 St./kg

Mehr Bilder zu "OEC 44 micro"

