

Order number: 202500001

Open text field 1:



- USB recording function and media player for various formats
- Pre-programmed channel lists - Watch TV immediately without a programme scan
- Electronic programme guide (EPG)
- DiSEqC™ 1.0/1.2/USALS, SCR unicable (EN 50494) and SCD2 (EN50607)
- Videotext decoder
- Mains switch
- Additional features
- Reception of digital satellite TV and radio programmes in DVB-S2 (HDTV) and DVB-S transmission standard
- Video decoding of MPEG-2 and MPEG-4-/H.264 signals (HDTV)
- Upscaler for scaling up the PAL signal to 576p, 720p, 1080i and 1080p
- Electrical audio output for Dolby Digital data stream (AC 3)
- Eight pre-programmed favourite programme lists each for TV and radio Suitable for software updates (operating software and channel list separately) via satellite and USB stick
- Language selection for programmes transmitted in multiple languages
- On-screen display (OSD) in eight languages (DE, GB, FR, IT, ES, CZ, NL, PL, TR)
- 4000 programme memory positions
- Display of images (jpeg) via USB
- Stand-by: < 0.5 W
- 4-character display



Hersteller: Kathrein

UFS 810 plus

Product information "UFS 810 plus"

DVB-S(2) receiver, HDTV FTA, PVR-Ready, 4-character display, HDMI, EPG, AC-3 opt., DiSEqC™ 1.0 and 1.2, SCR unicable, SCD2, black

Type:	UFS 810 plus
Order no.:	202500001
Colour:	Black
HF range:	-----
Sat IF band:	950-2150 MHz
Input level range:	44-83 dBµV
TV system video:	-----
Modulation, FEC, demultiplexer:	DVB-S/DVB-T standard
Video decoding:	MPEG-2, MPEG-4/H.264
Input data rate:	2-45 (30 bei DVB-S2/8PSK) MSymb/s
Video resolution:	CCIR 601 (720 x 576 Zeilen), 576i, 576p, 720p, 1080i, 1080p
S/N (Video):	> 53 dB
TV system audio:	-----
Decoding:	AC 3, MPEG-1, Layer 1, 2
Sampling rate:	32/44,1/48 kHz
S/N (Audio):	> 65 dB
Power supply:	-----
Power supply voltage:	230 (+/- 10 %)/50-60 V/Hz
Power consumption (max./typical operation/stand-by):	12/6/0,5 W
LNB supply (horiz./vert.):	14/18; Max. 500 V/mA
Control signal:	22 kHz; DiSEqC™ 1.0/1.2, SCR-Einkabel (EN 50494) und SCD-2 (EN 50607)
Connections:	-----
Sat IF input:	1 x F socket
Audio output (digital):	1 x optisch
Video/audio output (digital):	1 x HDMI
USB:	1 x 2.0
Scart:	1 x Buchse
General information:	-----
Ambient temperature:	Max. +5 to +40 °C
Unit dimensions (W x H x D):	180 x 40 x 100 mm
Weight:	0,29 kg

Mehr Bilder zu "UFS 810 plus"

