


Order number: 20510035

Open text field 1:

- Two-way tap and two-way distributor for the sat IF distribution system (4 x sat IF)
- For signal distribution in very large sat IF systems with 5-way multi-switch cascades
- Suitable for remote feeding via input <-> trunk output (4 x sat IF); isolating capacitors at tap outputs)
- For indoor installation
- Two-way tap, e.g. for connection of two 5-way multi-switch cascades to one trunk line
- Five two-way taps (4 x sat IF and 1 x terr. range) in a single housing
- Cascadable with other EAX 2512 or EBX 2520



Hersteller: Kathrein

EAX 2512

Product information "EAX 2512"

Sat IF tap - 5-862 and 4 x 950-2150 MHz - 5 x 2-way tap 12 dB in one housing - F connectors - Cascadable with EXR 5-way multi-switch system

Type:	EAX 2512
Order no.:	20510035
Inputs:	1 x terrestrial / 4 x Sat IF
Connection loss (input -> tap/splitter output):	12 / 13 -> 11 ¹⁾ dB
Trunk decoupling:	- / 50 dB
Max. remote feed current per satellite frequency plane:	1000 mA
Frequency range:	5-862 / 950-2150 MHz
Through loss (input -> trunk output):	1,5 -> 2 ¹⁾ / 0,8 -> 1,5 ¹⁾ dB
Tap/splitter output decoupling:	30 / 30 dB
Connections:	F connectors
Dimensions (W x H x D):	112 x 148 x 54,5 mm
Packaging unit/weight:	1 (10)/0.39 pc/kg

¹⁾ Frequency-dependent attenuation

Mehr Bilder zu "EAX 2512"

