


Order number: 21610006

Open text field 1:



- Nominal impedance 75 Ω
- Frequency range: 5-2400 MHz
- Suitable for remote feeding: Max. 24 V/0.5 A
- Without decoupling diodes, thus lower voltage drop
- Connections: F connectors
- Potential equalisation connection
- Compact dimensions
- Compliant with: EN 60728-11 and EN 50083-2
- For indoor installation
- Specially for use in unicable systems
- Note:

Supplied DC voltage is available at all connections. Only to be used in conjunction with ESU 33 ... 37. Unused outputs must be terminated with EMK 05 terminating resistor



Hersteller: Kathrein

EBC 110

Product information "EBC 110"

Two-way F distributor 5-2400 MHz, screening class A, potential equalisation connection, remote feeding max. 24 V/0.5 A (2 outputs), without decoupling diodes

Type:	EBC 110
Order no.:	21610006
Through loss 5-10 MHz/10-862 MHz/862-2150 MHz/2150-2400 MHz:	4/5/6/8 dB
Decoupling 5-10 MHz/10-862 MHz/862-2150 MHz/2150-2400 MHz:	10/20/18/16 dB
Dimensions:	51 x 59 x 26 mm
Packaging unit/weight:	1 (10, 200)/0.073 pc/kg